

TECHNICAL DATA: MULTI-PURPOSE DICERS

		<b>MS 84.2/MS 90</b>	<b>MS 84.3/MS 90.3</b>	<b>MS 100/MS 105</b>	<b>MS 100.3/MS 105.3</b>	<b>MS 120 JM</b>
Throughput:	kg/h	850.000	1.000	1.150	1.300	2.000
<i>(with highest feed and chamber filling)</i>						
Connected Load	kW	1,85	1,85	1,85	1,85	2,6
Chamber length	mm	310	530	370	530	530
Chamber's cross section	mm	90 x 90	90 x 90	105 x 105	105 x 105	126 x 126
Grid set's cross section	mm	84 x 84	84 x 84	100 x 100	100 x 100	120 x 120
<b>Grid set's cross section</b>	mm	<b>90 x 90</b>	<b>90 x 90</b>	<b>105 x 105</b>	<b>105 x 105</b>	
Cutting length mm		0 – 32	0 – 32	0 – 32	0 – 32	0 – 42
<i>(infinitely variable)</i>						
Longitudal		variable	variable	variable	variable	variable
Pre-compression		4 – side	4 – side	4 – side	4 – side	4 – side
<b>side pre-compression</b>		<b>without</b>	<b>without</b>	<b>without</b>	<b>without</b>	
side pre-compression	mm	1.158	1.560	1.280	1.550	1.550
Length	mm	639	639	690	690	720
Width	mm	1.079	1.079	1.090	1.120	1.120
Weight	kg/h	235	275	270	285	295

